

अनुरक्षण एवं अभियांत्रिकी इकाई MAINTENANCE & ENGINEERING UNIT भाकृअनुप-भारतीय कृषि अनुसंधान संस्थान ICAR-INDIAN AGRICULTURAL RESEARCH INSTITUTE नई दिल्ली-१२ NEW DELHI-12.



No. 174-18/20-21/ M.E. Unit

Dated : 30-09-2021

e-TENDER NOTICE

Online quotation are hereby invited on behalf of the Director, IARI from the Contractors Registered with CPWD, MES, Railways, MCD, PWD or other Central/State Govt./Semi Govt. The contractor must have valid PAN and GST registration number and having experience of two similar nature of works in last three years for the work mentioned below:

Name of work & location	Estimated cost (\mathbf{x})	Earnest Money (₹)	Last date & time of bid	Date & time of
Essential and emergent repair works in			submission	bid opening
type, I, II, III and IV type qtrs, at IARI New Delhi-110012.	₹ 4,88,225.00	₹ 10000.00	Upto14:30 hours 21.10.2021	22.10.2021 at15:00 hours

₹ 10,000/- (Rupees Ten Thousand Only) should be in the form of D.D./Pay Order/Fixed Deposit Receipt/Bank Guarantee from commercial bank drawn in favour of **Director**, **IARI** payable at New Delhi. The original EMD and cost of tender ₹ 500/- (Rupees five hundred only) in the form of DD/PO drawn in favour of Director, IARI payable at New Delhi shall be submitted to the Tender Inviting Authority on or before the last date and time of online bid submission. The details of D.D./Pay Order/Fixed Deposit Receipt/Bank Guarantee physically sent, should tally with the details available in the scan copy and the data entered during the online bid submission time otherwise the uploaded bid will be rejected.

The Online Tender Documents are available on IARI Website www.iari.res.in. & Central Portal www.eprocure.gov.in. Bids are to be submitted on central portal i.e. www.eprocure.gov.in.

Asstt. Admn. Officer (Works)

No: 174-18/20-21/ M.E. Unit

Name of the work: Essential and emergent repair works in type, I, II, III and IV type qtrs, at IARI New Delhi-110012.

ESTIMATE/SCHEDULE OF WORK

S. No.	ESTIMATE/SCHEDUL Particular		Rate	Unit	Amount
<u>3. No.</u> 1.	Repair of structural member by dismantling lose	Qty 20	1250.00	Sqm	25000.00
1.		20	1230.00	Sqm	25000.00
	concrete, treatment of existing reinforcement by 443 gum naffufill BB2: 2.2 kg cement spray per				
	sqm/, blinding of 50 x 50 4mm hard drawn fabric				
	mesh filling the spoil area by 1:3 (1 cement 3				
	coarse sand) i/c Dr. fixit (LW) mix with mortar @ 1				
	kg/50 kg cement & finishing the surface in finishing				
	in finishing as per the direction of Engineer In-				
	Charge.				
2.	Repairs to plaster of thickness 12 mm to 20 mm in	20	417.80	Sqm	8356.00
	patches of area 2.5 sq.meters and under, including				
	cutting the patch in proper shape, raking out joints				
	and preparing and plastering the surface of the				
	walls complete, including disposal of rubbish to the				
	dumping ground, all complete as per direction of				
	Engineer-in-Charge.				
	14.1.1 With cement mortar 1:4 (1 cement : 4 fine				
3.	sand) 15.56 Dismantling old plaster or skirting raking out	100	39.00	Sqm	3900.00
э.	joints and cleaning the surface for plaster including	100	57.00	Julia	5700.00
	disposal of rubbish to the dumping groundwithin 50				
	metres lead.				
4.	8.31 Providing and fixing Ist quality ceramic glazed	80	1030.30	Sqm	82424.00
••	wall tiles conforming to IS: 15622 (thickness to be	00	1000000	Sqiii	02121000
	specified by the manufacturer), of approved make,				
	in all colours, shades except burgundy, bottle				
	green, black of any size as approved by Engineer-				
	in-Charge, in skirting, risers of steps and dados,				
	over 12 mm thick bed of cement mortar 1:3 (1				
	cement : 3 coarse sand) and jointing with grey				
	cement slurry @ 3.3kg per sqm, including pointing				
	in white cement mixed with pigment of matching				
	shade complete.				
5.	11.39 Providing and laying rectified Glazed Ceramic	20	1088.40	Sqm	21768.00
	floor tiles of size 300x300 mm or more (thickness to				
	be specified by the manufacturer), of 1 st quality				
	conforming to IS: 15622, of approved make, in				
	colours White, Ivory, Grey, Fume Red Brown, laid				
	on 20 mm thick cement mortar 1:4 (1 Cement: 4				
	Coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white				
	cement and matching pigments etc., complete.				
	soment and matering pigments etc., complete.				
6.	Kota stone slab flooring over 20 mm (average) thick	50	1531.85	Sqm	76592.50
	base laid over and jointed with grey cement slurry				
	mixed with pigment to match the shade of the slab,				
	including rubbing and polishing complete with base				
	of cement mortar 1 : 4 (1 cement : 4 coarse sand) :				
	11.26.1 25 mm thick	10	450.00		FAC4 <0
7.	9.141 Providing and fixing PVC Door Frame of size	12	456.80	М	5481.60
	50x47 mm with a wall thickness of 5 mm (± 0.2 mm) made out of single piece extruded PVC				
	mm), made out of single piece extruded PVC profile, with mitred cut joints and joint with 2 nos of				
	PVC bracket of size 190 mm x 100 mm long arms				
	I VO DIACKEL UL SIZE 130 IIIII X TUU IIIII IUIIY AIIIIS				

	of cross section size 35 x 15 mm & self driven self taping screws, the vertical door profiles to be reinforced with 40x20 mm M.S. rectangular tube of 0.8 mm, including providing EPDM rubber gasket weather seal throughout the frame, including jointing 5 mm PVC frame strip with PVC solvent cement on the back of the profile. The door frame to be fixed to the wall using 8 x100 mm long anchor fasteners complete, all as per manufacturer's specification and direction of Engineer -in- charge.				
8.	35 mm thick factory made Solid panel PVC Door shutter, made out of single piece extruded solid PVC profiles, 5 mm (\pm 0.2 mm) thick, having styles & rails (except lock rail) of size 95 mmx 35 mm x 5 mm, out of which 75 mm shall be flat and 20 mm shall be tapered (on both side), having one side thickness of 15 mm integrally extruded on the hinge side of the profile for better screw holding power, including reinforcing with MS tube of size 40 mm X 20 mm x 1 mm, joints of styles & rails to be mitered cut & joint with the help of PVC solvent cement, self driven self tapping screws & M.S. rectangular pipes bracket of size 190 mm X 100 mm of cross section size 35 mm x 17 mm x 1 mm at each corner. Single piece extruded 5 mm thick solid PVC Lock rail of size 115 mm x 35 mm, out of which 75 mm to be flat and 20 mm to be tapered at both ends, having 15 mm solid core in middle of rail section integrally extruded, fixing the styles & rails with the help of solvent and self driven self tapping screws of 125 mm x 11 mm, including providing 5 mm Single piece solid PVC extruded sheet inserted in the door as panel, all complete as per manufacturer's specification and direction of Engineer-in-charge. 9.142.2 Decorative finish (wood grained finish)	6.4	3842.85	Sqm	24594.24
9.	Providing and fixing 1mm thick M.S. sheet door with frame of 40x40x6 mm angle iron and 3 mm M.S. gusset plates at the junctions and corners, all necessary fittings complete, including applying a priming coat of approved steel primer. 10.5.2 Using flats 30x6mm for diagonal braces and central cross piece	2.50	4278.15	Sqm	10695.38
10.	Dismantling G.I. pipes (external work) including excavation and refilling trenches after taking out the pipes, manually/ by mechanical means including stacking of pipes within 50 metres lead as per direction of Engineer-in-charge : 15.44.1 15 mm to 40 mm nominal bore	50	108.15	М	5407.50
11.	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. 18.8.2 20 mm nominal outer dia Pipes	90	478.15	М	43033.50
12.	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing	2	5260.95	No	10521.90

	cistern, including flush pipe, with manually ontrolled				
	device (handle lever), conforming to IS : 7231, with				
	all fittings and fixtures complete, including cutting				
	and making good the walls and floors wherever				
	required :				
	17.2.1 W.C. pan with ISI marked white solid plastic				
	seat and lid				
	Providing and fixing water closet squatting pan	2	5421.50	NO	10843.00
	(Indian type W.C. pan) with 100 mm sand cast Iron				
	P or S trap, 10 litre low level white P.V.C. flushing				
	cistern, including flush pipe, with manually				
	controlled device (handle lever) conforming to IS :				
	7231, with all fittings and fixtures complete,				
	including cutting and making good the walls and				
	floors wherever required:				
	17.1.1 White Vitreous china Orissa pattern W.C.				
	pan of size 580x440 mm with integral type foot				
	rests				
	13.80 Providing and applying white cement based	100	115.15	Sqm	11515.00
	putty of average thickness 1 mm, of approved				
	brand and manufacturer, over the plastered wall				
	surface to prepare the surface even and smooth				
	complete.				
	13.91 Removing dry or oil bound distemper, water	100	18.25	Sqm	1825.00
	proofing cement paint and the like by scrapping,				
	sand papering and preparing the surface smooth				
	including necessary repairs to scratches etc.				
	complete.				
	Distempering with 1st quality acrylic distemper	100	87.15	Sqm	8715.00
	(ready mixed) having VOC content less than 50				
	gms/litre, of approved manufacturer, of required				
	shade and colour complete, as per manufacturer's				
	specification.				
	13.42.1 Two or more coats on new work			~	
17.	Distempering with 1st quality acrylic distember	500	54.30	Sqm	27150.00
	(Ready mix) having VOC content less than 50 grams/				
	litre of approved brand and manufacture to give an				
	even shade :				
	13.90.1 Old work (one or more coats)	00	05.55	G	5000.00
	Finishing walls with Premium Acrylic Smooth	80	97.75	Sqm	7820.00
	exterior paint with Silicone additives of required				
	shade				
	13.112.1 Old work (Two or more coats applied @				
	1.43 ltr/ 10 sqm) over existing cement paint surface		< < n =	G	4.444.4.4.4
	B- Finishing walls with Premium Acrylic Smooth	200	66.95	Sqm	13390.00
	exterior paint with Silicone additives of required				
	shade				
	13.112.2 Old work (one or more coats applied @				
	0.83 ltr/10 sqm).	400	R A A R	C	
	Painting with synthetic enamel paint of approved	100	79.95	Sqm	7995.00
	brand and manufacture of required colour to give an				
	even shade :				
	13.99.1 One or more coats on old work		0.0.0.7		
	Providing and fixing aluminium tower bolts, ISI	20	90.00	No	1800.00
	marked, anodised (anodic coating not less than				
	grade AC 10 as per IS : 1868) transparent or dyed				
	to required colour or shade, with necessary screws				
	etc. complete :				
	9.97.3 200x10 mm	4.0	001 F.		
	Providing and fixing aluminium sliding door bolts,	10	231.70	No	2317.00
	ISI marked anodised (anodic coating not less than				
	grade AC 10 as per IS : 1868), transparent or dyed				

	to required colour or shade, with nuts and screws etc. complete : 9.96.2 250x16 mm				
22.	Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : 9.100.1 125 mm	40	59.65	No	2386.00
23.	Repair of old door shutter i/c refixing, cutting welding & change of hinges etc. complete as putty direction of engineer in-Charge.	4	500.00	No	2000.00
24.	17.16A Providing and fixing 8 mm dia C.P. / S.S. Jet with flexible tube upto 1 metre long with S.S. triangular plate to Eureopean type W.C. of quality and make as approved by Engineer - in - charge.	2	297.55	No	595.10
25.	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels 8.2.2.2 Area of slab over 0.50 sqm.	5	4007.65	Sqm	20038.25
26.	Providing and fixing Stainless Steel A ISI 304 (18/8) kitchen sink as per IS:13983 with C.I. brackets and stainless steel plug 40 mm, including painting of fittings and brackets, cutting and making good the walls wherever required : 17.10.1.1 510x1040 mm bowl depth 250 mm	1	5155.95	No	5155.95
27.	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require: 17.7.1 White Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps	2	3087.70	No	6175.40
28.	17.31 Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete.	2	1283.05	No	2566.10
29.	Lifting of malba by mechanical truck @300 per truck beyond 20km load at an appropriate dinping site i/c loading, unloading complete as per the direction of Engineer In-Charge.	2	3000.00	No	6000.00
30.	22.5 Providing and laying water proofing treatment in sunken portion of WCs, bathroom etc., by applying cement slurry mixed with water proofing cement compound consisting of applying : (a) First layer of slurry of cement @ 0.488 kg/sqm mixed with water proofing cement compound @ 0.253 kg/ sqm. This layer will be allowed to air cure for 4 hours. (b) Second layer of slurry of cement @ 0.242 kg/sqm mixed with water proofing cement compound @ 0.126 kg/sqm. This layer will be	20	465.60	Sqm	9312.00

	allowed to air cure for 4 hours followed with water curing for 48 hours.				
31.	11.44 Crazy ceramic tile flooring, with under layer 12 mm thick cement mortar 1:4 (1 cement: 4 coarse sand), with joints not exceeding 5 mm, including filling the gaps with ordinary cement mixture & mixing with synthetic polyester fibre, triangular in shape having specific gravity of 1.34 to 1.40, cross section size ranging from 10 to 40 micron & length upto 6 mm, mixing fibre @ 125 grams per 50 kg of cement in cement mortar, including providing and mixing water proofing material in mortar @ 1 kg per 50 kg of cement, all complete as per direction of Engineer-in-charge.	20	735.65	Sqm	14713.00
32.	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931 18.53.1 15mm nominal bore	5	532.00	No	2660.00
33.	Providing and fixing C.P. brass stop cock (concealed) of standard design and of approved make conforming to IS:8931. 18.52.1 15 mm nominal bore	2	606.25	No	1212.50
34.	Providing and fixing C.P. brass long nose bib cock of approved quality conforming to IS standards and weighing not less than 810 gms. 18.50.1 15 mm nominal bore	4	618.80	No	2475.20
35.	18.53A Providing and fixing C.P. Brass extension nipple (size 15mmx50mm) of approved make and quality as per direction of Engineer-in-charge.	4	61.25	No	245.00
36.	Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete :	4	386.40	No	1545.60
				Say Total	4,88,225.00

Subject to the following terms & conditions:-

- 1. The work shall be executed as per CPWD specifications.
- 2 Income Tax, work Tax & work cess as per norms shall be recovered from the bill.
- 3 1% water and electrical charges will be recovered from the bill if supplied by the Department.
- 4 The work shall start within 7 days from the date of award and complete within One month for a particular quarter failing which a penalty @1% per week delay will be imposed on the bill amount maximum upto 10%. The work shall remain continue for a period of one year.
- 5 All the material, laboures, T & P etc. required will be arranged by the firms itself.
- 6 Any other item to be required at site to complete the work be executed as per lowest quoted rates. On DSR-2018 & MR. If a revised sanction may also be accorded if amount exceeding the sanction value.
- 7 The Director, IARI has the right to reject any or all the quotations/tenders without assigning any reason.

Name of Signature of the Agency:

(Vikas Kumar) Junior Engineer/ T-3 Unit (Er. CHARAN SINGH) Chief Tech. Officer (Civil), ME

Special Instructions to the Contractors/Bidders for the e-submission of the bids online through this e-Procurement Portal

- 1. Bidder should do Online Enrolment in this Portal using the option Click Here to Enroll available in the Home Page. Then the Digital Signature enrolment has to be done with the e-token, after logging into the portal. The e-token may be obtained from one of the authorized Certifying Authorities such as eMudhraCA/GNFC/IDRBT/MtnlTrustline/SafeScrpt/TCS.
- 2. Bidder then logs into the portal giving user id / password chosen during enrolment.
- 3. The e-token that is registered should be used by the bidder and should not be misused by others.
- 4. DSC once mapped to an account cannot be remapped to any other account. It can only be Inactivated.
- 5. The Bidders can update well in advance, the documents such as certificates, purchase order details etc., under My Documents option and these can be selected as per tender requirements and then attached along with bid documents during bid submission. This will ensure lesser upload of bid documents.
- 6. After downloading / getting the tender schedules, the Bidder should go through them carefully and then submit the documents as per the tender document, otherwise, the bid will be rejected.
- 7. The BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevant coulmns, else the bidder is liable to be rejected for that tender. Bidders are allowed to enter the Bidder Name and Values only.
- 8. If there are any clarifications, this may be obtained online through the e-Procurement Portal, or through the contact details given in the tender document. Bidder should take into account of the corrigendum published before submitting the bids online.
- 9. Bidder, in advance, should prepare the bid documents to be submitted as indicated in the tender schedule and they should be in PDF/XLS/RAR/DWF formats. If there is more than one document, they can be clubbed together
- 10. Bidder should arrange for the EMD as specified in the tender. The original should be posted/couriered/given in person to the Tender Inviting Authority, within the bid submission date and time for the tender
- 11. The bidder reads the terms and conditions and accepts the same to proceed further to submit the bids.
- 12. The bidder has to submit the tender document(s) online well in advance before the prescribed time to avoid any delay or problem during the bid submission process.
- 13. There is no limit on the size of the file uploaded at the server end. However, the upload is decided on the Memory available at the Client System as well as the Network bandwidth available at the client side at that point of time. In order to reduce the file size, bidders are suggested to scan the documents in 75-100 DPI so that the clarity is maintained and also the size of file also gets reduced. This will help in quick uploading even at very low bandwidth speeds.
- 14. It is important to note that, the bidder has to Click on the Freeze Bid Button, to ensure that he/she completes the Bid Submission Process. Bids Which are not Frozen are considered as Incomplete/Invalid bids and are not considered for evaluation purposes.
- 15. In case of Offline payments, the details of the Earnest Money Deposit(EMD) document submitted physically to the Department and the scanned copies furnished at the time of bid submission online should be the same otherwise the Tender will be summarily rejected.
- 16. The Tender Inviting Authority (TIA) will not be held responsible for any sort of delay or the difficulties faced during the submission of bids online by the bidders due to local issues.
- 17. The bidder may submit the bid documents online mode only, through this portal. Offline documents will not be handled through this system.
- 18. At the time of freezing the bid, the e-Procurement system will give a successful bid updation message after uploading all the bid documents submitted and then a bid summary will be shown with the bid no, date & time of submission of the bid with all other relevant details. The documents submitted by the bidders will be digitally signed using the e-token of the bidder and then submitted.
- 19. After the bid submission, the bid summary has to be printed and kept as an acknowledgement as a token of the submission of the bid. The bid summary will act as a proof of bid submission for a tender floated and will also act as an entry point to participate in the bid opening event.

- 20. Successful bid submission from the system means, the bids as uploaded by the bidder is received and stored in the system. System does not certify for its correctness.
- 21. The bidder should see that the bid documents submitted should be free from virus and if the documents could not be opened, due to virus, during tender opening, the bid is liable to be rejected.
- 22. The time that is displayed from the server clock at the top of the tender Portal, will be valid for all actions of requesting bid submission, bid opening etc., in the e-Procurement portal. The Time followed in this portal is as per Indian Standard Time (IST) which is GMT+5:30. The bidders should adhere to this time during bid submission.
- 23. All the data being entered by the bidders would be encrypted at the client end, and the software uses PKI encryption techniques to ensure the secrecy of the data. The data entered will not be viewable by unauthorized persons during bid submission and not viewable by any one until the time of bid opening. Overall, the submitted bid documents become readable only after the tender opening by the authorized individual.
- 24. During transmission of bid document, the confidentiality of the bids is maintained since the data is transferred over secured Socket Layer(SSL) with 256 bit encryption technology. Data encryption of sensitive fields is also done.
- 25. The bidders are requested to submit the bids through online eProcurement system to the TIA well before the bid submission end date and time (as per Server System Clock.

List of Documents to be scanned and uploaded within the period of bid submission:

- 1. Demand draft / Pay order / FDR / Bank Guarantee of any Scheduled Bank against EMD.
- 2. Receipt of EMD & Tender Fee.
- 3. Certificate of Registration for GST.
- 4. Copy of PAN.
- 5. Enlistment of CPWD, MES, Railways, MCD, PWD or other Central/State Govt./Semi Govt.
- 6. Experience of two similar nature of works in last three years.

MAINTENANCE & ENGINEERING UNIT ICAR-INDIAN AGRICULTURAL RESEARCH INSTITUTE NEW DELHI-12.

No. - / - /ME Unit

Dated :

Prescribed format of receipt of deposition of original EMD/Tender Fee

(This receipt shall also be uploaded with technical bid to the e-tendering website by the intending bidder upto the specified bid submission date and time.)

1.	Name of work
2.	Tender ID
3.	Estimated Cost
4.	Amount of Earnest money deposit
5.	Last date of submission of bid
6.	Agency Name
7.	EMD (No. & Date)
8.	Tender Fee (No. & Date)

Tender Inviting Authority ICAR-IARI-ME Unit

CERTIFICATE TO BE SIGNED BY THE TENDERER

It is certified that I have read and understood and will comply with all instructions contained in Terms & conditions of this tender documents. All pages submitted with this tender document from page _____ to _____ have been filled properly and signed with seal of the firm/company.

Signature of tenderer:
Name in block letters:
Name of firm:
Full address:

1)	Telephone No. :
ii)	Mobile No. :
iii)	Fax No. :
iv)	Email ID :

Signature of Tenderer with office seal