

ALL INDIA NETWORK PROJECT ON PESTICIDE RESIDUES

Room No. 203, 2<sup>nd</sup> Floor, B-2 Block, LBS Building ICAR- Indian Agricultural Research Institute, New Delhi –110 012

File No. ICAR-IARI/AINP/LC-MS/MS/23-24/14

15/12/2023

## NOTICE FOR E-PROCUREMENT THROUGH GEM

On-line Bids on Gem are invited from reputed Manufactures/Supplier/Authorized dealer in two bid system (Technical bid & Financial bid) for purchase of following scientific Equipment on behalf of Director, ICAR-Indian Agricultural Research Institute, New Delhi. The last date for submission of Bid is 03.01.2024 at 4:00PM. The bid will be opened on 03.01.2024 at 4:30 PM by the prescribed committee.

Please visit <u>www.iari.res.in</u> for details Rules and Regulation and log in <u>www.qem.qov.in</u> for online bidding.

S.No	Name of the Scientific Equipment	Qty.	Earnest Money	Cost of th Equipment	ne
1	LC-MS/MS with Accessories	01	8,75,000/-	1,75,00,000/-	

Detail of Gem Bid (Tender) are mentioned below:

Gem Bid (Tender) No.	GEM/2023/B/4336214	
Bid Submission start date & time	13/12/2023 at 5:05AM	
Last date & time for submission of bid	03/01/2024 at 4:00PM	
Date & time for opening of technical bid	03/01/2024 at 4:30PM Rs.1,75,00,000/-	
Cost of estimated bid value (in Rupees)	Rs. 1,75,00,000/-	
Pre-Bid date and Time	20/12/2023 at 11:00AM	
Pre-Bid Venue	AINP on Pesticide Residue, Room No. 203, 2 <sup>nd</sup> Floor, B-2 Block, LBS Building, ICAR- IARI, New Delhi-110 012	

## LC-MS/MS specifications:

1

Solvent Delivery System	Quaternary Pump
	Degasser
	Flow Range: $0.001 - 2.0$ ml/min or better
	Operating Pressure: 0-15000 Psi at 1 ml/min or more
	Flow Rate Precision: 0.08% RSD or less
Autosampler	Standard Sample Capacity: Minimum 80 vials of 1.5 ml or 2 ml
	capacity or better
	Temperature Control Range: 4 – 40 °C
	Standard Injection Range: $1 - 50 \mu l$ or better
	Carry over should be less than 0.005% or better
Column Heater	Ambient plus 5 °C to 80 °C or better
MS/MS System	Triple Quadrupole based system with dedicated ESI and APCI ionization source as standard part of the system capable of carrying out MS and MS/MS experiment. Mass Range: 10 amu to 2000 amu or better
Resolution	Mass Resolution 1 Da or less
Electronics	
Electronics	Polarity switching switch from positive to negative polarity should
N. C. 1 '1'	be 25 milli second or less
Mass Stability	Less than 0.1 Da over a period of 24 hours
Scan Speed	18000 amu/sec or better
Collision Cell	Dwell time 1 milli second or less
Sensitivity	Positive Electron Spray ionization (ESI) positive: minimum S/N ratio of 5,00,000: 1 for 1 pg on column injection of Reserpine (official technical specification sheet should be attached).
	The negative Electron Spray ionization (ESI) mode should also give the minimum S/N ratio of 5,00,000: 1 for 1 pg on column injection of chloramphenicol (official technical specification sheet should be attached).
	OR
	Instrument Detection Limit (IDL) less than 4 fg reserpine in ESI
	positive mode and chloramphenicol in ESI negative mode.
Scan Modes	Should be capable of performing MS Scan, Product Ion Scan, SIM, MRM, Neutral loss/gain scan, Precursor Ion Scan.
	Should also be capable of Full Scan MSMS
Computer and Software	Branded PC with i7 processor, 24 "LED Screen, 1 TB HDD, 16
<b>T</b>	GB RAM etc.) and colour laser jet printer.
	Quote database for minimum 1000 contaminants including
	pesticide, antibiotics, mycotoxins etc. pertaining to their Molecular
	formula, mono isotopic mass, parent ion, collision energy, product
	ion, Rt, Sensitivity, ion ratio etc.
	Original company licensed latest software having capabilities to
	perform the following functions.

Network Coordinator A.I.M.P. on Pesticide Residues Room No. 203, B - 2 Block, USS Stuilding ICAN-Indian Agricultural Research Inscisie

	A) Automated calibration and quantitative optimization.
	B) Perform alternating Positive/Negative scans in one run.
	C) Automated quantitation and reporting of acquired samples.
	During the warranty period, the supplier shall provide the original
	version of any updates to the system software / new software
	launched at no extra cost.
Gas Generator/ Gas	A suitable extremely low noise and vibration free imported gas N2
Cylinder	generator with built in air compressor
	One-time supply of filled cylinder of any other required gas, with
	regulator required for functioning of Mass Spectrometer
Accessories	Suitable On-Line 10 KVA UPS (Numeric/APC or equivalent),
	with suitable batteries for atleast 2 hr back up with full load
	UPLC C-18 columns:
	$10$ cm $\times$ 2.1mm, sub 2 microns (2 no.) $10$ cm $\times$ 4.6mm, 3-3.5
	microns (2 no.) along with guard cartridge and guard column (2
	each for both columns)
Warranty	The warranty period shall be 60 months from the date of
	completion of supply, installation and completion of all incidental
	services OR 62 months from the date of delivery in case the
	installation & all incidental services cannot be completed within 02
	months from the date of delivery on account of the Consignee.
	Warranty should include all spares parts, electronic parts & boards,
	hardware consumables like PM kits, generator.
ť	
	Accessories listed in the technical specifications will be initially
	provided by the suppliers along with the equipment. Thereafter, it
	will be the responsibility of the consignee to provide the same as
	and when required.
	Other conditions of warranty clause remain the same.
×	Performance Bank Guarantee (PBG) of 3%- 62 months from the
	date of installation
Qualification Tests	The company should perform IQ, PQ and OQ tests with
Quannearion resis	documentation at the time of installation
Calibration	The company should bring the calibration kit and perform the
	annual calibration of the equipment during the warranty period.
Schedule of requirement	At least 2 days onsite training of the analysts after every 6 months
para iv(f) On-site training	during the warranty period
Eligibility Criteria	Vendor should have supplied minimum 10 Installation of quoted
Englomity Chiena	model in India. Installation reports to be submitted and 5
	satisfactory performance certificates from the customer should be
	provided for the quoted model.
Payment clause	100% payment after successful installation & demonstration.

