

अनुरक्षण एवं अभियांत्रिकी इकाई MAINTENANCE & ENGINEERING UNIT भाकृअनुप-भारतीय कृषि अनुसंधान संस्थान ICAR-INDIAN AGRICULTURAL RESEARCH INSTITUTE नई दिल्ली-१२ NEW DELHI-12.



No. 32-65/23-24/ME Unit

Dated: 22.02.2024

e-TENDER NOTICE

Online quotation are hereby invited on behalf of the Director, IARI from the Contractors Registered with CPWD, MES, Railways, MCD, PWD or other Central/State Govt./Semi Govt. The contractor must have valid PAN and GST registration number and having experience of two similar nature of works in last three years for the work mentioned below:

Name of work & location	Estimated cost (₹)	Last date & time of bid	Date & time of bid
Modification of room no. 24 into lab, division		submission	opening
of Genetics IARI PUSA, New Delhi12.	₹ 3,34,496.00	Upto14:30	14.03.2024
		hours	at15:00 hours
		13.03.2024	

The Online Tender Documents are available on IARI Website www.iari.res.in. & Central Portal www.eprocure.gov.in . Bids are to be submitted on central portal i.e. www.eprocure.gov.in

Admn. Officer (Works)

				32-65/2	3-24/MEU
	Modification of room no. 24 into lab, division of Genetics IARI PUSA, New Delhi	L 2 .			
S.No.	Particular	Qty	Unit	Rate	Amount
1	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting				
	the patch in proper shape, raking out joints and preparing and plastering the surface of the walls				
	complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in- Charge.				
	With cement mortar 1:4 (1cement: 4 coarse sand)	5.00	sqm	478.00	2390
2	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.	32.00	sqm	45.05	1442
3	Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead :				
	Of area 3 sq. metres and below	2.00	each	302.7	605
4	Making opening in brick wall upto 0.50sqm by demolishing brick work, as per the direction of engineer-in-	1			
	charge.	1.00	each	2000	2000
5	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in				
	superstructure above plinth level up to floor V level.				
	Cement mortar 1:4 (1 cement :4 coarse sand)	6.00	sqm	1018.05	6108
6	Making chases up to 7.5x7.5 cm in walls including making good and finishing with matching surface after				
	housing G.I. pipe etc.	8.00	Rm	171.80	1374
7	Centering and shuttering including strutting, propping etc. and removal of form for				
	Shelves (Cast in situ)	7.50	sqm	766.55	5749
8	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all				
	complete above plinth level.				
	Thermo-Mechanically Treated bars of grade Fe-500D or more.	160.00	kg	89.65	14344
9	Reinforced cement concrete work in beams, suspended floors, roofsmhaving slope up to 15° landings,				
	balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level				
	up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement with 1:1.5:3 (1				
	cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size				
	derived from natural sources).	0.70	cum	10719.30	7504

10	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for				
	kitchen platforms, vanity counters, window sills, facias and similar locations of required size,				
	approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand),				
	joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing,				
	moulding and polishing to edges to give high gloss finish etc. complete at all levels.				
	Granite stone slab all colour and texture except black, Cherry/Ruby red. Area of slab upto 0.50 sqm	10.00	sqm	3555.45	35555

11	12 mm cement plaster of mix : 1:4 (1 cement: 4 coarse sand)	30.00	sqm	307.25	9218
12	Providing and fixing Ist quality ceramic glazed Digital wall tiles of size 300 mm x 600 mm of Digital type				
	conforming to IS : 15622 (thickness to be specified by the manufacture) of approved make in all colours,				
	shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of				
	steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey				
	cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade				
	complete.	35.00	sqm	1450.00	50750
13	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with				
	water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades,				
	laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/				
	sqm including grouting the joints with white cement and matching pigments etc., complete. Size of Tile				
	600x600 mm	15.00	sqm	1416.65	21250
14	Providing and fixing tiled false ceiling of specified materials of size 595x595 mm in true horizontal level,				
	suspended on inter locking metal grid of hot dipped galvanized steel sections (galvanized @ 120 grams/ sqm,				
	both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size				
	24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of				
	size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm				
	center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size 24x25 mm				
	made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids				
	of 600x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture in the grid				
	including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke				
	detectors etc. Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x1.6				
	mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanised				
	butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottom exposed				
	width of 24 mm of all T-sections shall be pre-painted with polyester paint, all complete for all heights as per				
	specifications, drawings and as directed by Engineer-in-charge.				
	12.5 mm thick square edge PVC Laminated Gypsum Tile of size 595x595 mm, made of Gypsum plasterboard,				
	manufactured from natural gypsum as per IS 2095 part I and laminated with white 0.16mm thick fire retardant				
	PVC film on the face side and 12micron metalized polyester on the back side with all edges sealed with the face				
	side PVC film which goes around and wraps the edges and is bonded to the edges and the back side metalized				
	polyester film so as to make the tile a completely sealed unit.	14.50	sqm	1948.95	28260

15	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up				
	standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733				
	and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at				
	junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections				
	shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle,				
	Aluminium snap beading for glazing/paneling, C.P. brass / stainless steel screws, all complete as per				
	architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be				
	paid for separately) :				
	For fixed portion				
	Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic				
	coating of grade AC 15)	25.00	kg	433.95	10849
16	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision				
	for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings				
	shall be paid for separately) Powder coated aluminium (minimum thickness of powder coating 50 micron)				
		60.00	kg	564.80	33888
17	Providing and fixing ACP sheet in panelling fixed in aluminum doors, windows shutters and partition frames				
	with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineerin-				
	charge.	2.00	sqm	1000.00	2000
18	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM				
	rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of				
	engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):				
	With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)	1.00	sqm	1325.55	1326
19	Providing and fixing aluminium round shape handle of outer dia 100 mm with SS screws etc. complete as per				
	direction of Engineer-incharge				
	Powder coated aluminium (minimum thickness of powder coating 50 micron)	6.00	each	101.00	606
20	Providing and fixing aluminium tower bolts, ISI marked, Powder coated aluminium (minimum thickness of				
	powder coating 50 micron or dyed to required colour or shade, with necessary screws etc. complete :100x10				
	mm	2.00	each	190.00	380
	250x10 mm	4.00	each	410.00	1640
21	Providing and fixing ISI marked aluminium butt hinges Powder coated aluminium (minimum thickness of				
	powder coating 50 micron) dyed to required colour or shade with necessary screws etc. complete:100x63x4				
	mm	8.00	each	110.00	880
22	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting,				
	hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted				
	with special shaped washers etc. complete.				
	Hot finished welded type tubes	50.00	kg	154.90	7745

	G. Total				356073
	Add GST @ 6.33%				21198
	ΤΟΤΑΙ				334876
	Engineer-in-charge.	1.00	trip	3000.00	3000
	capacity, including loading, transporting, unloading to approved municipal dumping ground or approved by		per		
27	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by truck of 5cum				
	New work (two or more coats) over and including water thinnable priming coat with cement primer	60.00	sqm	162.55	9753
26	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade :				
25	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	45.00	sqm	123.85	5573
	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	45.00	sqm	20.85	938
23	P/f of wooden wall rack of depth upto 2feet with shutters made of 19mm thick board or glass whichever required, laminated with 1mm thick lamination sheet outside and inside provision of shelves and partition alongwith the provision of fixing over the wall including making all necessary arrangements, as pe the direction of engineer-in-charge.	45.00	sqft	1550	69750

Subject to be following terms & conditions:-

1. The work shall be executed as per CPWD specifications.

2. Income Tax, work Tax & work cess as per norms shall be recovered from the bill.

3. 1% water and electrical charges will be recovered from the bill if supplied by the Department.

4. The work shall start within 7 days from the date of award and complete within 45 days failing which a penalty @ 1% per day delay will be imposed on the bill amount maximum upto 10%.

5.All the materials, laboures, T&P etc. required will be arranged by the firms itself.

6.Any other item to be required at site to complete the work will be executed as per the lowest quoted rates on DSR-2021.

7. The rates shall remain valid for 90 days from the date of opening of quotations/tenders.

8. A running payment may be made of athe successful completion of work for 1/2nd or more amount of work.

9. The Director, IARI has the right to reject any or all the quotation/tenders without assigning any reason.

Special Instructions to the Contractors/Bidders for the e-submission of the bids online through this e-Procurement Portal

- 1. Bidder should do Online Enrolment in this Portal using the option Click Here to Enroll available in the Home Page. Then the Digital Signature enrolment has to be done with the e-token, after logging into the portal. The e-token may be obtained from one of the authorized Certifying Authorities such as eMudhraCA/GNFC/IDRBT/MtnlTrustline/SafeScrpt/TCS.
- 2. Bidder then logs into the portal giving user id / password chosen during enrolment.
- 3. The e-token that is registered should be used by the bidder and should not be misused by others.
- 4. DSC once mapped to an account cannot be remapped to any other account. It can only be Inactivated.
- 5. The Bidders can update well in advance, the documents such as certificates, purchase order details etc., under My Documents option and these can be selected as per tender requirements and then attached along with bid documents during bid submission. This will ensure lesser upload of bid documents.
- 6. After downloading / getting the tender schedules, the Bidder should go through them carefully and then submit the documents as per the tender document, otherwise, the bid will be rejected.
- 7. The BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevant coulmns, else the bidder is liable to be rejected for that tender. Bidders are allowed to enter the Bidder Name and Values only.
- 8. If there are any clarifications, this may be obtained online through the e-Procurement Portal, or through the contact details given in the tender document. Bidder should take into account of the corrigendum published before submitting the bids online.
- 9. Bidder, in advance, should prepare the bid documents to be submitted as indicated in the tender schedule and they should be in PDF/XLS/RAR/DWF formats. If there is more than one document, they can be clubbed together
- 10. Bidder should arrange for the EMD as specified in the tender. The original should be posted/couriered/given in person to the Tender Inviting Authority, within the bid submission date and time for the tender
- 11. The bidder reads the terms and conditions and accepts the same to proceed further to submit the bids.
- 12. The bidder has to submit the tender document(s) online well in advance before the prescribed time to avoid any delay or problem during the bid submission process.
- 13. There is no limit on the size of the file uploaded at the server end. However, the upload is decided on the Memory available at the Client System as well as the Network bandwidth available at the client side at that point of time. In order to reduce the file size, bidders are suggested to scan the documents in 75-100 DPI so that the clarity is maintained and also the size of file also gets reduced. This will help in quick uploading even at very low bandwidth speeds.
- 14. It is important to note that, the bidder has to Click on the Freeze Bid Button, to ensure that he/she completes the Bid Submission Process. Bids Which are not Frozen are considered as Incomplete/Invalid bids and are not considered for evaluation purposes.
- 15. In case of Offline payments, the details of the Earnest Money Deposit(EMD) document submitted physically to the Department and the scanned copies furnished at the time of bid submission online should be the same otherwise the Tender will be summarily rejected.
- 16. The Tender Inviting Authority (TIA) will not be held responsible for any sort of delay or the difficulties faced during the submission of bids online by the bidders due to local issues.
- 17. The bidder may submit the bid documents online mode only, through this portal. Offline documents will not be handled through this system.
- 18. At the time of freezing the bid, the e-Procurement system will give a successful bid updation message after uploading all the bid documents submitted and then a bid summary will be shown with the bid no, date & time of submission of the bid with all other relevant details. The documents submitted by the bidders will be digitally signed using the e-token of the bidder and then submitted.
- 19. After the bid submission, the bid summary has to be printed and kept as an acknowledgement as a token of the submission of the bid. The bid summary will act as a proof of bid submission for a tender floated and will also act as an entry point to participate in the bid opening event.
- 20. Successful bid submission from the system means, the bids as uploaded by the bidder is received and stored in the system. System does not certify for its correctness.
- 21. The bidder should see that the bid documents submitted should be free from virus and if the documents could not be opened, due to virus, during tender opening, the bid is liable to be rejected.
- 22. The time that is displayed from the server clock at the top of the tender Portal, will be valid for all actions of requesting bid submission, bid opening etc., in the e-Procurement portal. The Time followed in this portal is as per Indian Standard Time (IST) which is GMT+5:30. The bidders should adhere to this time during bid submission.
- 23. All the data being entered by the bidders would be encrypted at the client end, and the software uses PKI encryption techniques to ensure the secrecy of the data. The data entered will not be viewable by unauthorized persons during bid submission and not viewable by any one until the time of bid opening. Overall, the submitted bid documents become readable only after the tender opening by the authorized individual.
- 24. During transmission of bid document, the confidentiality of the bids is maintained since the data is transferred over secured Socket Layer(SSL) with 256 bit encryption technology. Data encryption of sensitive fields is also done.
- 25. The bidders are requested to submit the bids through online eProcurement system to the TIA well before the bid submission end date and time (as per Server System Clock.

The following documents (Scan copy) must be furnished upload with the technical bid failing which tender will not be accepted at all.

- 1. GST/ PAN card copy
- 2. Registration certificate of CPWD, MES, Railways, MCD, PWD or other Central/State Govt./Semi Govt.
- 3. Certificate declaring that the firm has not been debarred/Black listed by the Govt. Deptt./Court of law for doing any business in India.
- 4. Bid Security Declaration Document
- 5. The tender documents duly signed by the concerned firm accepting the same should be attached with technical bid.
- 6. The firm should have experience of two similar nature of works in last three years. Firm should submit experience certificate/ orders in support.

FORMAT OF BID SECURITY DECLARATION FROM BIDDERS IN LIEU OF EMD (On Bidders Letter head)

- ➤ That I / we have availed the benefit of waiver of EMD while submitting our offer against the subject Tender and no EMD being deposited for the said tender.
- That in the event we withdraw/modify our bid during the period of validity Or I/we fail to execute formal contract agreement within the given timeline OR I/we fail to submit a Performance Security within the given timeline Or I/we commit any breach of Tender Conditions/ Contract which attracts penal action of forfeiture of EMD and I/we will be suspended from being eligible for bidding / award of all future contract(s) of ME Unit, Directorate, IARI, New Delhi-11012 for a period of one year from the date of committing such breach.

Signature and Seal of Authorised Signatory of bidder

Name of Authorized Signatory.....

Company Name.....

CERTIFICATE TO BE SIGNED BY THE TENDERER

It is certified that I have read and understood and will comply with all instructions contained in Terms & conditions of this tender documents. All pages submitted with this tender document from page _____ to _____ have been filled properly and signed with seal of the firm/company.

Signature of tenderer:
Name in block letters:
Name of firm:
Full address:

i)	Telephone No. :
ii)	Mobile No. :
iii)	Fax No. :
iv)	Email ID :

Signature of Tenderer with office seal